

**KMS Technologies – KJT Enterprises Inc.**

**Presentation**

**Strack, K. – M.**

**1998 – 1999**

**Through Casing Resistivity  
Measurements**

**Society of Petroleum Engineers  
Distinguished Lecture**


# Through Casing Resistivity Measurements



SPE distinguished lecture

K.-M. Strack


KMS Technologies (sponsored by Baker Atlas)




1998-1999

WALS96623a

## Colorado Test: known test zone



## Colorado Test: known test zone



BA965207k-2


# Basic History

- Three electrode scheme
- Modern design
- WA feasibility study
- Colorado test
- PML acquisition by BA
- First digital log, BA Texas
- Alpin (1939)
- Kaufman (1990)
- Vail (1991)
- May-Nov. 1993
- Dec. 1993-Mar. 1994
- Q4 1997
- 5/98



BA98213b

# TCR - Project Components




# Producer Consortium

- Phillips
- Mobil
- ARCO
- Texaco
- Chevron
- Shell
- BP
- Conoco


Scope: Act as mentor during the development activities (interpretation)

# TCR Principle of Operation



BA98213c

# Operational Modes



WALS96623h

## TCR tools at Baker Atlas test well



BA98213d

# Typical Signal Levels for Electrical Logging Tools

Laterolog  
tool

Induction  
tool

TCR

Sensor Voltage




nanovolt


microvolt

millivolt

# Amplifier Noise





# Vertical Resolution Test




WALS965207c-II

# Casing Shoe & Reservoir Depletion



BA9652071-2

# Logging process




Earth model described  
by parameters  
(resistivity distribution)

AWS951357

KS92


# Modeling process for logs



Modeling



Logs



Inversion




Earth model described  
by parameters  
(resistivity distribution)

AWS951357

KS92


# Inversion: Process flow




WALS98208u

# Casing Collar Effect (resistive)

Feasibility Study



Test well



BA9652070


J. E. Taylor - May 3.

PML Test Well

41

## Delta T (AOP)

Confidential




Printed Out: 8/26/03

Printed Out: 8/26/83


$$R_{app} = \frac{Q(230) \cdot T(230) \Delta t}{\Delta T(230)}$$

$$\begin{array}{l} \text{P(230)} = 0.28 (\text{P.9}) \\ \text{IT(230)} = 1.935 (\text{P.3}) \\ \delta T(230) = 0.011 (\text{P.11}) \\ \text{AP(PD)} = 0.503 \text{ N} \end{array} \quad \left| \begin{array}{l} \text{Papp} = \frac{0.28 \cdot 1.935}{0.011} = \\ \text{27.8} - \text{Compressive} \\ \text{P.12 -} \\ \text{P'KAN} \end{array} \right.$$

# Frequency Limit




## Skin Depth/Casing Thickness Distribution for Different Casing Types, Diameters, Temperature, and Thickness




WALS965209


# TCR Interpretation




# Colorado Test: Blind Test Zone



# Induction - TCR inversion comparison




# Inversion Results




# WALS test well


## First digital log

### 5/98



WALS965207k-2





# **Summary**

- TCR works
- Numerical modeling predicted results
- Test well data matches induction logs
- TCR service feasible

## **Acknowledgements:**

**C. Anderson, L. Campbell, W. Chaffe, O.N. Fanini, H,  
Haines, J. Hunziker, S. Momii, R. Siegfried, L.A.  
Tabarovsky, T. Tamarchenko, W.B. Vail, T. Wang,  
B.Sh. Zinger**

**Gas Research Institute**

**TCR Consortium: Arco, BP, Chevron, Conoco, Mobil,  
Phillips, Texaco, Shell**

# The places 1998

Brisbane



Miri




Kuala Lumpur




Perth




Melbourne




# The Places 1998 continued



# The Places 1998 continued



TCR presentations



KMS Technologies – KJT Enterprises Inc.  
6420 Richmond Ave., Suite 610  
Houston, Texas, 77057, USA  
Tel: 713.532.8144

[info@kmstechnologies.com](mailto:info@kmstechnologies.com)

Please visit us  
<http://www.kmstechnologies.com//>